

# VAC-S18U HDMI DISTRIBUTION AMPLIFIER

## [ MENU ]

- CHANNEL SELECT
- INPUT SETTINGS
- OUTPUT SETTINGS
- INPUT AUDIO SETTINGS
- OUTPUT AUDIO SETTINGS
- EDID SETTINGS
- LAN SETTINGS
- SYSTEM SETTINGS

## VIEW STATUS

## [ VIEW STATUS ]

INPUT STATUS	VIDEO STATUS	: IN			
	FORMAT	: 3840x2160p 59.94Hz			
	INPUT MODE	: HDMI MODE			
	HDCP	: HDCP 2.2 Type0			
	COLOR SPACE	: 422 LIMITED RANGE YUV709			
	DEEP COLOR	: 24 BIT COLOR			
	SCRAMBLE	: SCRAMBLE ON			
	AUDIO STATUS	: IN			
	FORMAT	: LINEAR PCM			
	SAMPLING FREQUENCY	: 48 kHz			
	CHANNEL	: 2 CHANNEL			
	BIT LENGTH	: 24 BIT			
SINK DEVICE STATUS		: OUT1	OUT2	OUT3	OUT4
<input type="button" value="OUT1 - OUT4"/> ▼	HDCP AUTHENTICATION	: HDCP 2.2 Type 0	HDCP 2.2 Type 0	HDCP 2.2 Type 0	HDCP 2.2 Type 0
	OUTPUT MODE	: HDMI MODE	HDMI MODE	HDMI MODE	HDMI MODE
	COLOR SPACE	: 422	422	422	422
	COLOR RANGE	: LIMITED RANGE	LIMITED RANGE	LIMITED RANGE	LIMITED RANGE
	DEEP COLOR	: 24 BIT COLOR	24 BIT COLOR	24 BIT COLOR	24 BIT COLOR
	SCRAMBLE	: SCRAMBLE ON	SCRAMBLE ON	SCRAMBLE ON	SCRAMBLE ON
SINK DEVICE EDID		: OUT1	OUT2	OUT3	OUT4
	MONITOR NAME	: HDC-RH421UHD	ICP-401UHD	MSD-802UHD	VAC-S12U
	RESOLUTION	: 3840x2160 594.00MHz	3840x2160 594.00MHz	3840x2160 594.00MHz	3840x2160 594.00MHz
	HDMI/DVI	: HDMI MODE	HDMI MODE	HDMI MODE	HDMI MODE
	COLOR SPACE	: RGB / 422 / 444 / 420	RGB / 422 / 444 / 420	RGB / 422 / 444 / 420	RGB / 422 / 444 / 420
	DEEP COLOR	: 24 BIT COLOR	24 BIT COLOR	24 BIT COLOR	24 BIT COLOR
	PCM FREQUENCY	: 32 / 44 / 48 kHz	32 / 44 / 48 kHz	32 / 44 / 48 kHz	32 / 44 / 48 kHz
	PCM BIT LENGTH	: 16 / 20 / 24 BIT	16 / 20 / 24 BIT	16 / 20 / 24 BIT	16 / 20 / 24 BIT
	PCM CHANNEL	: 2 CHANNEL	2 CHANNEL	2 CHANNEL	2 CHANNEL
	COMPRESSED AUDIO	: NOT SUPPORTED	NOT SUPPORTED	NOT SUPPORTED	NOT SUPPORTED
	HDR	: NOT SUPPORTED	NOT SUPPORTED	NOT SUPPORTED	NOT SUPPORTED
	SCDC	: SUPPORTED	SUPPORTED	SUPPORTED	SUPPORTED
	3D	: NOT SUPPORTED	NOT SUPPORTED	NOT SUPPORTED	NOT SUPPORTED
SYSTEM STATUS	TEMPERATURE	: 42.5 C			
	POWER	: 12.102 V			
VERSION	VAC-S18U	: 01.00.00			

# VAC-S18U HDMI DISTRIBUTION AMPLIFIER

## [ MENU ]

CHANNEL SELECT

INPUT SETTINGS

**OUTPUT SETTINGS**

INPUT AUDIO SETTINGS

OUTPUT AUDIO SETTINGS

EDID SETTINGS

LAN SETTINGS

SYSTEM SETTINGS

VIEW STATUS

## [ OUTPUT SETTINGS ]

OUT1

OUT2

OUT3

OUT4

OUT5

OUT6

OUT7

OUT8

SIGNAL FORMAT:

FOLLOW SINK DEVICE

ALL

EDID ERR OUTPUT MODE:

OFF

ALL

HOTPLUG MASK:

OFF  ON

2

2sec - 15sec

ALL

DOWN CONVERSION:

FOLLOW SINK DEVICE

DDC POWER CONTROL:

ON  OFF

0

0sec - 60sec

ALL

OUTPUT SIGNAL:

SOURCE ON

ALL

# VAC-S18U HDMI DISTRIBUTION AMPLIFIER

[ MENU ]

CHANNEL SELECT

INPUT SETTINGS

OUTPUT SETTINGS

INPUT AUDIO SETTINGS

OUTPUT AUDIO SETTINGS

EDID SETTINGS

LAN SETTINGS

SYSTEM SETTINGS

VIEW STATUS

[ CHANNEL SELECT ]

OUTPUT SIGNAL:

OUT1

SOURCE ON ▾

EXECUTION

OUT2

SOURCE ON ▾



OUT3

SOURCE ON ▾

OUT4

SOURCE ON ▾

OUT5

SOURCE ON ▾

OUT6

SOURCE ON ▾

OUT7

SOURCE ON ▾

OUT8

SOURCE ON ▾

NAME EDIT:

NAME EDIT