

THX-1200-SW

12" THX® Ultra2™ Certified
Passive Subwoofer



THE THX-1200-SW IS A COMPACT, HIGH-OUTPUT, LOW-DISTORTION PASSIVE SUBWOOFER

It is suitable for use in any high-performance home-theater or music system. A pair of THX-1200-SW's driven by a KA-1000-THX amplifier meet all requirements for THX Ultra2 certification. Although a single THX-1200-SW does not satisfy the stringent THX Ultra2 maximum output specification, which assumes a very large room, it is more than adequate for a typical small or medium-sized room. Either configuration is capable of intense, powerful deep-bass reproduction, with no loss of clarity or detail at even the highest levels demanded by modern action-movie soundtracks. The cabinet is front-ported to maximize installation flexibility.

THE THX-1200-SW IS BUILT AROUND A CASTFRAME, LONG-THROW DRIVER WITH A 12-INCH CERAMETALLIC™ CONE.

Propelling it is a powerful motor structure with a huge, 240-ounce magnet. This rugged, no-compromise driver is capable of staggering output without breakup or distortion.

CONSTRUCTION IS TO THE HIGHEST STANDARD

With a professional grade rabbet and dado locked panel cabinet and premium components throughout to ensure sonic purity, consistency, and reliability. Each subwoofer enclosure has a NL2 SpeakOn™ input for correct, secure amplifier connections, and each THX-1200-SW is supplied with a 20-foot THX Ultra certified speaker cable terminated with NL2 SpeakOn connectors.

- Very high output capability (130dB @ 30Hz)
- 12" Cerametallic cast-frame, long-throw driver with 240-ounce magnet structure
- Front-ported enclosure for maximum installation flexibility
- NL2 SpeakOn inputs for correct, secure amplifier connection

SPECIFICATIONS

FREQUENCY RESPONSE	20-200Hz ± 3dB
MAX ACOUSTIC OUTPUT	130dB @ 30Hz, 122dB @ 20 Hz, 112dB @ 15Hz 1/8 space, 1 Meter (2 enclosures side-by-side per THX Ultra2)
NOMINAL IMPEDANCE	8 ohms compatible
ENCLOSURE TYPE	Bass-reflex via front-firing slot port
AMPLIFIER	Use only with KA-1000-THX
ENCLOSURE TYPE	Sealed
AMPLIFIER POWER	See KA-1000-THX specifications
WOOFER	12" (30.5cm) front firing, Cerametallic™ cone, cast aluminum frame driver with a 240oz ceramic magnet structure
DIMENSIONS	20.25" (51.4cm) H x 17.75" (45.1cm) W x 17.75" (45.1cm) D (w/grille)
WEIGHT	80 lbs. (36kg)
ENCLOSURE MATERIAL	Medium density fibreboard construction (MDF)
FINISH	Galaxy Black cabinet with Black anodized aluminum fascia



Klipsch®
KEEPERS OF THE SOUND

3502 WOODVIEW TRACE INDIANAPOLIS, IN 46268 | KLIPSCH.COM/CUSTOM

All specifications are subject to change without notice. ©2019 Klipsch Group, Inc. Klipsch, Keepers of the Sound and Tractrix are registered trademarks of Klipsch Group, Inc. a wholly-owned subsidiary of Vox International Corporation.